

Harness Inspection Hazard Checklist

	Hazard Mitigation	Satisfactory	Needs Attention	Not Applicable	Target Date for Completion	Date Completed
1	The user of the harness has been properly trained to inspect the harness.					
2	Inspection tags are legible, up-to-date, and secure.					
3	Other required labels and warnings are legible and securely fastened.					
4	The manufacturer's instructions available.					
5	The self-retracting lifeline (SRL) or 'yo-yo's', impact indicator shows signs of activation.					
6	The webbing straps are free from frayed edges, broken fibers, pulled stitching, and cuts.					
7	There is no discoloration on the webbing from UV light or indication of burns, friction, chemical damage or mold.					
8	Paint, dirt or other residue buildup degrading the webbing integrity is not present.					
9	The stich patterns are complete without stitching missing.					
10	The stitching is not undone and does not have any rips or pulls.					
11	There are not any additional holes punched in the webbing.					
12	There are not any cuts or tears in webbing around the grommets.					
13	All of the pads are in good condition free from tears, frays, cracks or damage.					
14	The grommets are tightly set in the webbing.					
15	The grommets are not bent and are free from damage.					
16	The grommets are free and unbroken from rotation.					
17	None of the D-Rings is broken, damaged, distorted or showing signs of unusual wear.					
18	None of the D-Rings have cracks, breaks, corrosion, or rough/sharp edges.					
19	The D-Rings pivot and move freely.					
20	The D-Rings are secured to the harness.					
21	The buckles do not have unusual wearer damage.					
22	The buckles work freely and click when buckles engage.					

Actions Taken to Correct Items Checked as "Needs Attention"						
Hazard #						
Hazard #						
Hazard #						
Hazard #						
Hazard #						
	Name	Date				

The above evaluations and/or recommendations are for general guidance only and should not be relied upon for medical advice or legal compliance purposes. They are based solely on the information provided to us and relate only to those conditions specifically discussed. We do not make any warranty, expressed or implied, that your workplace is safe or healthful or that it complies with all laws, regulations or standards.

For more information, visit: $\underline{www. SafeAtWorkCA.com}$



Lanyard Inspection Hazard Checklist

	Hazard Mitigation	Satisfactory	Needs Attention	Not Applicable	Target Date for Completion	Date Completed
1	The snap hooks and/or carabineers do not have any noticeable damage, distortion, sharp edges, burrs, cracks, corrosion, discoloration or bends.					
2	The locking mechanisms on snap hooks and carabineers self-close, lock and function correctly.					
3	The markings on the snap hooks and carabineers are legible.					
4	The webbing does not have any cuts, burns, tears, abrasions, frays, excessive soiling or any other signs of damage.					
5	The webbing or rope does not have any knots.					
6	There is not any sign of Ultraviolet damage on the webbing or rope (indicated by discoloration, splinters and/or slivers on the surface).					
7	The webbing does not have any pulled or cut stitching.					
8	The webbing is not visibly damaged.					
9	The synthetic rope does not have any frays, broken strands, cuts, burns, abrasions, excessive soiling, any buildup from any type of substance such as paint or any other signs of damage.					
10	All the splices in the ropes are tight and thimble ends are held secure in the splice.					
11	The thimble end does not have any cracks or damage.					
12	The energy-absorbing component does not have any elongation, tears and excessive soiling.					
13	The energy-absorbing pack does not have any holes, tears or signs of deployment.					
14	The stitching on the energy-absorbing pack are free from tears.					
15	The load indicator is deployed.					
16	All of the labels are securely held in place and they are legible.					
17	The lanyard has not been modified.					
18	This is the appropriate lanyard for the job and task being performed (length, type, etc.).					
19	The user of this lanyard received the required and necessary training.					

Actions Taken to Correct Items Checked as "Needs Attention"						
Hazard #						
Hazard #						
Hazard #						
Hazard#						
Hazard #						
	Name	Date				

The above evaluations and/or recommendations are for general guidance only and should not be relied upon for medical advice or legal compliance purposes. They are based solely on the information provided to us and relate only to those conditions specifically discussed. We do not make any warranty, expressed or implied, that your workplace is safe or healthful or that it complies with all laws, regulations or standards.

For more information, visit: www.SafeAtWorkCA.com



Anchorage Hazard Checklist

	Hazard Mitigation	Satisfactory	Needs Attention	Not Applicable	Target Date for Completion	Date Completed
1	The manufacturer's instructions for proper anchor set-up has been read and is understood.					
2	The anchorage plate does not show any physical damage including cracks, sharp edges, burrs or deformities/bent metal.					
3	The anchor plate does not show any excessive corrosion which could affect the operation.					
4	When inspecting the anchor, all markings legible.					
5	If a webbing anchor is used, there are not any cuts, burns, holes, UV damage, excessive wear, or writing on the webbing.					
6	The anchor point is installed per the manufacturer's instructions. NOTE: Pay particular attention to the number of screws needed, the types of screws required to be used, and what material the anchor must be secured to.					
7	The anchor can support at least 5,000 pounds per employee attached.					
8	The number of people attached to the anchor meets the manufacturer's specifications.					
9	The anchor has been secured above where the employee will be working or at least not lower than the employee's waist.					
10	You are moving the anchor as an employee moves to another area of an elevated work surface or installing additional anchors to protect against swing angle exposures.					
	Actions Taken to Correct Items Checked as	"Ne	eds	Att	ention"	
	Hazard #					
Hazard # Hazard #						
Hazard #						
Hazard#						

The above evaluations and/or recommendations are for general guidance only and should not be relied upon for medical advice or legal compliance purposes. They are based solely on the information provided to us and relate only to those conditions specifically discussed. We do not make any warranty, expressed or implied, that your workplace is safe or healthful or that it complies with all laws, regulations or standards.

For more information, visit: www.SafeAtWorkCA.com

Name

Date